



www.xpeditecoatings.com

Xpedite HD Cleaner

DESCRIPTION

A biodegradable extra heavy-duty caustic liquid for heavy soil and grease removal. Its rapid cleaning action through mechanical equipment cuts grease and fat quickly.

DILUTION

It is usually diluted with hot water for best cleaning action.

General purpose 1/60 parts ratio

Soak cleaning 1/10 parts ratio

2 to 4 oz./gal with pressure washer, manual scrubbing or equipment.

A 1:1 ratio provides the most vigorous combination for cleaning the worst possible grime accumulation. However it may dull and even remove paint.

A dilution of 2 to 4 ounces per gallon through hot water pressure washer will quickly clean stainless steel tanks, cutting equipment, work benches, etc. Soak thoroughly, let stand for one minute, then pressure rinse.

Dilute 1 in 10 parts of hot water or soak to clean utensils, valves, etc.

WHERE TO USE

Industrial and commercial heavy duty cleaning, particularly in the food processing areas, meat rooms, maintenance garages, and heavy-duty degreasing.



PACKAGING

Xpedite HD Cleaner is available in 1 gallon and 5 gallon pails, and 55 gallon drums.

CAUTION

Follow the Hazardous Materials Identification System labeling guide for proper personal protective equipment to use when handling this product. Avoid contact with skins and eyes. If contact occurs, flush with water. If ingested do not induce vomiting; call a physician.

Always try product first in a small area to see results.

Do not use Xpedite HD Cleaner to clean magnesium metal. A strong concentration may discolor and soften many paints. Milder concentrations may be used on floors that are not as dirty.

KEEP OUT OF REACH OF CHILDREN